

Model Name	SE-2200
Product Name	HD/SD 6-Channel Digital Video Switcher
Video Standard	HD & SD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60 Hz 576i 50Hz, 480i 59.94Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
Input Routable / Crosspoint	All 6, repeatable
Video Input	6x HD-SDI, 2x HDMI (on CH5 & 6)
Mix HD & SD source	Selectable HD or SD
Computer Graphic Interface	2 via HDMI
Video output	6x SDI Outputs assignable: AUX 1-4, PGM, PVW, PGM Clean & multi-view 2x HDMI assignable: PGM or multi-view
Down-converted output	N/A
Built-in Multi-view monitoring out	2x HDMI
Audio input	4x Balanced XLR
Audio output	2x Balanced XLR
Embedded audio support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	N/A
A+V switching	Yes
Chromakey	N/A
Title Creator	Yes
USK	N/A
DSK	1x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Still Store	6

Effects	FTB, Cut, 8 Wipe with border
Transition Preview	PiP & DSK
Sync / Reference In/Out	Built-in Genlock (internal)
Tally Output	1x D-sub 25pin, dual color
PC Remote Control	Via Ethernet (free Window software) or RS-422 / RS-232
Built-in Audio Mixer	N/A
Special Features	6x6 Matrix seamless switch
Chassis	2 units, 2RU rack-mount mainframe
Power	DC 12V 32W
Accessory	CB-46/47/50 (30/50/100m)